

# BELL POLE SERIES



IP66	IK09	220-240V	5 YRS Warranty	20 - 60 WATTS
------	------	----------	-------------------	------------------

Upon request

1-10V	DALI
-------	------

## PHYSICAL

Body	Aluminum alloy
Finish	Powder coating
Dimensions	ø371xH420mm


## OPTICAL

Diffuser	Polycarbonate optical lens
Light distribution	More than 10 optics lens for optional

## ELECTRICAL

Light source	LED
CRI	>70
CCT	3000K, 4000K, 5000K
Driver	Electronic included   50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Operating Temperature	-30°C ~ +50°C
Humidity	10% ~ 90%RH

**BELL POLE** series aligns with the contemporary urban trend by incorporating sleek curvature, presenting a neat aesthetic, and ensuring effective heat dissipation. With a clear and fully rounded PC cover, it eliminates blind spots created by Light source arms, contributing to both safety and the visual appeal of urban spaces. It offers a range of control options, adding a touch of intelligence to the latest advancements in urban lighting solutions.




Range	Power (W)	Lumen (lm)
BELL POLE 1	20W	2400lm
BELL POLE 2	40W	4800lm
BELL POLE 3	60W	7200lm

## ORDERING CODE


SERIES NAME	PRODUCT RANGE	CCT	OPTICS	CONTROL	ACCESSORIES
BELL	1	30 3000K	BP01	1 ON-OFF	NS NEMA SOCKET
	2	40 4000K	BP02	2 1-10V	PC PHOTOCELL CONTROL
	3	50 5000K	BP03	3 DALI	SC SHORTING CAP
			BP04		MS MOTION SENSOR
			BP05		Z ZHAGA
			BP06		RC REMOTE CONTROL
			BP07		DC PC DIFFUSION COVER
			BP08		WA WALL MOUNT ADAPTOR




## AVAILABLE OPTICS




BP01




BP02




BP03




BP04




BP05



BP06



BP07



BP08

## ACCESSORIES



NEMA SOCKET



PHOTOCELL  
CONTROL



SHORTING CAP



BUILT IN  
MOTION  
SENSOR



ZHAGA



REMOTE  
CONTROL



PC DIFFUSION  
COVER



WALL MOUNT  
ADAPTOR