HIGH BAY PRO SERIES





PHYSICAL


Body	Aluminum Alloy
Finish	Powder Coating / Silver grey
Dimensions	ø400xH162mm
OPTICAL	
Optic	Polycarbonate
ELECTRICAL	
Light source	LED
CRI	>80 (Ra70 optional)
CCT	3000K,4000K,5000K
Driver	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver DALI, Daylight Sensor, Microwave Motio Sensor, PIR Sensor available.
Ambient Temp.	-30°C~ 50C°
Ambient Humidity	10% ~ 90%

Ambient Temp.	-30°C~ 50C°	
Ambient Humidity	10% ~ 90%	

HIGH BAY PRO SERIES is suitable for wholesale and distribution channels with simple design. Most importantly, the very low UGR<22, helps get the best performance, for offices, libraries, meeting areas.

Product Features:

- UGR<22
- Light efficiency:170lm/w
- Light sources and lanterns can be multi-choice power
- Built-in sensor
- Various accessories are available



Range	Power(W)	Lumen(lm)	
HIGH BAY PRO 1	100W	17000lm	
HIGH BAY PRO 2	120W	20400lm	
HIGH BAY PRO 3	150W	25500lm	_
HIGH BAY PRO 4	200W	34000lm	
•			_







ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - OPTICS - CONTROL

HIGH BAY PRO

I DALI 2 DAYLIGHT SENSOR 3 MICROWAVE MOTION SENSOR

4 PIR SENSOR

ACCESSORIES





Sensor





bracket







controller controller