## **NEON SIDE BEND LED STRIP 11.5 W/m**






Material	High quality FPC, UV and salt water resistant
Finish	White(outside) & Milky finish(over light emission)
Dimensions	L5000xW10xH10mm
Beam Angle	140°
Input Voltage	24Vdc
Power	11.52 W/m
Light source	LED
Lumen	330 lm/m
CRI	≥80
ССТ	3000K-4000K-6000K
Driver	24Vdc remote driver to be ordered separately
Cuttingn unit	50mm
Ambient Temp.	-20°C ~ 50°C

## **Product Features**

IP67 fully encapsulated, flexible LED strip for linear outdoor and indoor, LED circuit completely encapsulated with UV silicone sheath, no yellowish after years.

- -High quality FPC, UV & salt water resistant
- -Dot free and homogeneous light emission surface
- -Self-encapsulated LED
- -Light source lifetime:50K hours
- -Vertical bending
- -High quality silicone material
- -Min.Bending Diameter: 140mm
- -Single-ended power supply maximum length:10m
- -Cuttable each 50mm



## **Mounting Accessories**

Image	Description
11	Aluminum Profile: L2000xW11.7xH10.5mm
A September 1	10mm moldable profile
	Cutting accessories set (Front&end cap, power cord)
	PC mounting clips and screws

## **ORDERING CODE**

NEON SIDE BEND

SERIES NAME - CCT - CONTROL - ACCESSORIES

30 3000K I ON-OFF 40 4000K 2 I-10V 60 6000K 3 DALI I ALUMINUM PROFILE 2 MOLDABLE PROFIL:E 3 CUTTING ACCESSORIES

4 PC MOUNTING CLIPS AND SCREWS