

# QUADRANT SLIM POLE



IP68

IK09

220-240V

5 YRS  
Warranty

20 - 30  
WATTS

Upon request

1-10V

DALI

PHYSICAL

Body	Aluminium Extruded Profile
Finish	Polyester Powder Coated
Dimensions	L150xW100xH3000mm

OPTICAL

Diffuser	Clear Polycarbonate
Light distribution	2 ways light distribution

ELECTRICAL


Light source	LED
CRI	>70
CCT	3000K, 4000K, 5000K, 5700K
Driver	Electronic included   50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Operating Temperature	-40°C ~ +50°C
Humidity	10% - 90%RH

**QUADRANT SLIM POLE** series stands out as a dependable option for pathways, landscaped areas, and various public spaces, featuring a rectangular frame, and a 2-way light distribution.


- Glare is effectively minimized through a concealed light source.
- The 2 way light distribution not only efficiently illuminates pathways and areas but also introduces a distinctive visual effect.
- Various height options and a coordinating column make it suitable for high-end architectural projects.
- Its minimalistic design ensures seamless integration with diverse architectural styles.

Range	Power (W)	Lumen (lm)
QUADRANT SLIM POLE 1	20W	2700lm
QUADRANT SLIM POLE 2	25W	3175lm
QUADRANT SLIM POLE 3	30W	3600lm


AVAILABLE OPTICS



Type II Short-1



Type II Short-2



Type II Short-3

## ORDERING CODE

SERIES NAME	-	PRODUCT RANGE	-	CCT	-	OPTICS	-	CONTROL
QUADRANT SLIM POLE		1 2 3		30 3000K 40 4000K 50 5000K 57 5700K		1 TYPE II-1 2 TYPE II-2 3 TYPE II-3		1 ON-OFF 2 1-10V 3 DALI