


GLOBO BOLLARD



GLOBO BOLLARD series serves as an exceptional luminaire for urban settings, suitable for both new construction projects and retrofit applications. This versatile bollard light is available in heights of 0.5M and 1M.

- 360° Coverage and visual comfort.
- High lumen output efficiency, up to 130lm/W.
- The housing is made of 100% aluminum alloy.
- Outdoor powder coating for anti-corrosion.
- Easy to maintain.
- Robust design with IK10 protection.



ORDERING CODE

SERIES NAME - PRODUCT RANGE - HEIGHT - CCT - OPTICS - CONTROL

GLOBO I I TYPE I 30 3000K M MILKY 1 ON-OFF
 2 II TYPE II 40 4000K C CLEAR 2 1-10V
 50 5000K 3 DALI

IP66	IK10	220-240V	5 YRS Warranty	14/25 WATTS
------	------	----------	-------------------	----------------

Upon request

1-10V	DALI
-------	------

PHYSICAL

Body	Aluminum alloy
Finish	Powder Coated
Dimensions	Type I: Ø133xH500mm
	Type II: Ø133xH975mm

OPTICAL


Diffuser	Clear Polycarbonate (Milky PC cover available)
Light distribution	Assymetric

ELECTRICAL


Light source	LED
CRI	>80
CCT	3000K-4000K-5000K
Driver	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Operating Temperature	-30°C ~ + 45°C
Humidity	10% ~ 90%RH

Range	Power(W)	Lumen(lm) MILKY PC COVER	Lumen(lm) CLEAR OPTIC LENS
GLOBO 1	14W	1400lm	1820lm
GLOBO 2	25W	2500lm	3250lm

AVAILABLE OPTICS



MILKY PC COVER
LOW GLARE



CLEAR OPTIC
LENS