

BAMBOO SERIES



IP65	IK08	220-240V	5 YRS Warranty	20-60 WATTS
------	------	----------	-------------------	----------------

Upon request



PHYSICAL

Body	Polycarbonate
Finish	White

OPTICAL

Aiming	120°
Diffuser	Polycarbonate
CRI	>80

ELECTRICAL

Light source	LED LUMILEDS
Efficacy	160lm/W
CCT	3000K, 4000K, 6000K
Driver	220-240Vac
Ambient Temp.	-30°C - +50°C
Ambient Humidity	10% - 90%
Light source Life	>50,000 h

BAMBOO SERIES adopts high lumen SMD chip, the high transmittance PC cover makes a uniform and soft light output. With waterproof joint at both ends, it can be linkable. Special clip-on bracket design makes an easier installation. The installation angle is adjustable with different scales. This luminaire can be used in farm, factory, warehouse, workshop, and other lighting area with high humidity and dusty places. Pendant/ Surface mounted installation.

Series	Power (W)	Dimensions(mm)	Lumen(lm)
BAMBOO 1	20W	L600xW62xH74	3200lm
BAMBOO 2.1	40W	L1200xW62xH74	6400lm
BAMBOO 2.2	60W	L1200xW62xH74	9600lm
BAMBOO 3.1	36W	L1500xW62xH74	5760lm
BAMBOO 3.2	60W	L1500xW62xH74	9600lm

ORDERING CODE

SERIES NAME - PRODUCT RANGE - CCT - CONTROL			
BAMBOO	I	30 3000K	1 ON-OFF
	2.1	40 4000K	2 1-10V
	2.2	60 6000K	
	3.1		
	3.2		