

PANSY SERIES



PANSY SERIES is an anti-glare downlight, it adopts high lumen light source, deep reflector and low glare UGR<16, which provides a comfortable visual experience. The aluminum profile provides excellent thermal dissipation and ensures a long lifespan.

It is designed for general lighting applications in toilets, wash-rooms, hotels, shopping malls etc.

IP65

220-240V

5 YRS
Warranty

9-45
WATTS

LOW
GLARE

UGR
<16

Upon request

1-10V

DALI

PHYSICAL	
Body	Aluminum
Finish	White /Black
OPTICAL	
Diffuser	Polycarbonate
Beam Angle	24° (COB) / 60° (SMD)
ELECTRICAL	
Light source	LED COB/SMD
Lumen	85 lm/W
CRI	>80
CCT	2700K - 3000K - 4000K - 5000K - 6000K - 7000K
Driver	Electronic included 50-60Hz 220-240VAC Non-Dimmable Driver 1-10V dimming or DALI on request
Ambient Temp.	-25°C ~ 45°C
Ambient Humidity	10% ~ 90%
Light source Life	50,000 h



PANSY LE TR 80lm/W			
	Rated Power(W)	Lumen (lm)	LED
PANSY 1 LE TR	9W	720 lm	CREE
PANSY 2 LE TR	15W	1200 lm	CREE
PANSY 3 LE TR	24W	1920 lm	CREE
PANSY 4 LE TR	35W	2800 lm	CREE
PANSY 5 LE TR	45W	3600 lm	CREE
PANSY LE 85lm/W			
	Rated Power(W)	Lumen (lm)	LED
PANSY 1 LE	9W	765 lm	CREE
PANSY 2 LE	15W	1275 lm	CREE
PANSY 3 LE	24W	2040 lm	CREE
PANSY 4 LE	35W	2975 lm	CREE
PANSY 5 LE	45W	3825 lm	CREE
PANSY HE TR 90lm/W			
	Rated Power(W)	Lumen (lm)	LED
PANSY 1 HE TR	9W	810 lm	BRIDGELUX
PANSY 2 HE TR	15W	1350 lm	BRIDGELUX
PANSY 3 HE TR	24W	2160 lm	BRIDGELUX
PANSY 4 HE TR	35W	3150 lm	BRIDGELUX
PANSY 5 HE TR	45W	4050 lm	BRIDGELUX
PANSY HE 100lm/W			
	Rated Power(W)	Lumen (lm)	LED
PANSY 1 HE	9W	900 lm	BRIDGELUX
PANSY 2 HE	15W	1500 lm	BRIDGELUX
PANSY 3 HE	24W	2400 lm	BRIDGELUX
PANSY 4 HE	35W	3500 lm	BRIDGELUX
PANSY 5 HE	45W	4500 lm	BRIDGELUX

ORDERING CODE

SERIES NAME	PRODUCT RANGE	FINISH	CCT	CONTROL
PANSY	1 LETR	W WHITE	27 2700K	1 ON-OFF
	2 LETR	B BLACK	30 3000K	2 1-10V
	3 LETR		40 4000K	3 DALI
	4 LETR		50 5000K	
	5 LETR		60 6000K	
			70 7000K	
	1 LE			
	2 LE			
	3 LE			
	4 LE			
	5 LE			
	1 HETR			
	2 HETR			
	3 HETR			
	4 HETR			
	5 HETR			
	1 HE			
	2 HE			
	3 HE			
	4 HE			
5 HE				